



CHR<sup>®</sup> TAPE 

CHR<sup>®</sup> 2925/2995

Specialized for Extreme Conditions

## Glass-Foil Pressure Sensitive Adhesive Tape

CHR<sup>®</sup> 2925 and 2995-11R are manufactured from aluminium foil laminated to fibreglass cloth with high-temperature silicone adhesive on one side.

### Features/Benefits

CHR<sup>®</sup> 2925's high-temperature silicone adhesive allows the product to withstand continuous high temperatures, and prevents tape slippage after application. CHR<sup>®</sup> 2995-11R is formed by laminating 0.127 mm, dead soft aluminium foil to fibreglass fabric and applying a special blend of high-temperature silicone adhesives. The backing provides an excellent combination of strength, flexibility and heat resistance. Both 2925 and 2995-11R have excellent strength and flexibility, which provides easy wrapping of complex shapes and minimizes wrinkling.

### Availability

CHR<sup>®</sup> 2925 is available in 0.178 mm and 0.279 mm thicknesses, factory stock is in master rolls 33 m x 914 mm, and rolls can be slit in widths ranging from 6.35 mm to 914 mm. CHR<sup>®</sup> 2925 is available with or without a liner. CHR<sup>®</sup> 2995-11R is supplied on a clear polyester release liner. It unwinds easily, can be die-cut, and each roll is started with a pull-tab. Factory stock for 2995-11R is in master rolls 33 m x 914 mm, and rolls can be slit in widths ranging from 12.7 mm to 914 mm.

### Applications

CHR<sup>®</sup> 2925 performs as a plasma or flame spray masking tape, allowing areas to be free of grit blasting and the plasma spray coating. Its high-temperature resistance makes it ideal for heat and reflectant tapes, and it is used in aerospace and automotive markets as a wire harness bundling tape in engine components. CHR<sup>®</sup> 2925 also is used as a sound and vibration dampening product. CHR<sup>®</sup> 2995-11R is designed for extremely high demand thermal spray applications, such as HVOF and High Detonation Systems. It provides excellent abrasion and temperature resistance and conforms very well to a wide variety of surface configurations. The extremely aggressive adhesive system assures the tape stays in place throughout the entire coating process and will release cleanly after use, reducing the cleaning of the coated parts.



  
SAINT-GOBAIN

## CHR® 2925/2995 Properties

Performance tests are run using standard test procedures.  
The values presented are typical values and should not be used for specification purposes.

Product Number	2925-7	2925-11	2995-11R
Backing Material	Glass-Foil	Glass-Foil	Glass-Foil
Adhesive Type	Silicone	Silicone	Silicone
Total Thickness (mm)	0.178	0.279	0.305
Backing Thickness (mm)	0.064	0.191	0.178
Adhesive Thickness (mm)	0.114	0.089	0.127
Adhesion to Steel (N/cm)	6.6	8.2	4.9
Tensile Strength (N/cm)	228	350	263
Elongation (% at break)	7	7	5
Operating Temperature (°C)	-73 to +260	-73 to +260	-73 to +260
Colour	Aluminium	Aluminium	Aluminium

CHR® is a registered trademark.



### Saint-Gobain

AMERICAS  
Tel: (800) 962-2666  
(518) 686-7301

EUROPE  
Tel: +44 (0) 1706-746900

ASIA  
Tel: (886) 2-2503-4201

[www.foamsandtapes.saint-gobain.com](http://www.foamsandtapes.saint-gobain.com)

AMERICAS: 14 McCaffrey Street, Hoosick Falls, NY 12090, USA

EUROPE: Bay 3 Transpennine Industrial Estate, Gorrels Way, Rochdale, OL11 2PX, UK

ASIA: Room 302,3F-1, 147 Jianguo North Road, Section 2, Taipei, Taiwan, 104

The data and details in this document were correct and up-to-date at the time of printing and are intended to provide information on our products and their possible applications. It is the user's responsibility to obtain the latest version of the product data sheet. This data sheet is not a specification and does not assure specific product characteristics or make reference to the suitability of the product for a specific application. Because Saint-Gobain cannot anticipate or control every application, we strongly recommend testing of this product under individual application conditions. The application, use and conversion of this product are the user's responsibility.

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse or inability to use this product(s).

SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

NOTE: Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform their own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

2925&95-711R-EN-CHREU-RR-1605

©2016 Saint-Gobain Performance Plastics